

Agency Information

The certificate is only used for browsing on the web and proves that SETsafe | SETfuse has been certified.

If you need a FULL-VERSION certificate, please contact us: sales@SETfuse.com

该证书只用于在网页浏览，证明SETsafe | SETfuse已获得认证，如需要完整版本证书，请联系我们: sales@SETfuse.com

UL Product iQ®

JDYX2.E345932 - Fuses, Supplemental - Component

Fuses, Supplemental - Component

XIAMEN SET ELECTRONICS CO LTD
 8067 XIANG'AN XI RD XIAMEN TORCH
 HIGH-TECH INDUSTRIAL DEVELOPMENT ZONE
 XIANG'AN INDUSTRY DIST
 XIAMEN, FUJIAN 361101 China

E345932

Cat. No.	Size mm(in)	Amps (A)	Volts (V)	Interrupting Rating (A)
Supplemental fuses: pigtail leads, filled-tube				
SCF625Fx250V , Cartridge Type, x means rated current, 0.1A~20A	6.76 x 26.5 (0.27 x 1.04)	0.1-20	250Vac	10000
		0.1-20	400Vdc	2000
		0.1-30	400Vdc	300
		0.1-50	75Vdc	2500
SCF625Fx400VA , Cartridge Type, x means rated current, 0.1A~20A	6.76 x 26.5 (0.27 x 1.04)	0.1-20	250Vac	10000
		0.1-20	400Vdc	2000
		0.1-30	400Vdc	300
		0.1-50	75Vdc	2500
SCF625Fx400VD , Cartridge Type, x means rated current, 0.1A~30A	6.76 x 26.5 (0.27 x 1.04)	0.1-20	250Vac	10000
		0.1-20	400Vdc	2000
		0.1-30	400Vdc	300
		0.1-50	75Vdc	2500
SCF625Fx75V , Cartridge Type, x means rated current, 0.1A~50A	6.76 x 26.5 (0.27 x 1.04)	0.1-20	250Vac	10000
		0.1-20	400Vdc	2000
		0.1-30	400Vdc	300
		0.1-50	75Vdc	2500
SCF625PFx250V , Cartridge Type, x means rated current, 0.1A~20A	6.76 x 26.5 (0.27 x 1.04)	0.1-20	250Vac	10000
		0.1-20	400Vdc	2000
		0.1-30	400Vdc	300
		0.1-50	75Vdc	2500
SCF625PFx400VA , Cartridge Type, x means rated current, 0.1A~20A	6.76 x 26.5 (0.27 x 1.04)	0.1-20	250Vac	10000
		0.1-20	400Vdc	2000
		0.1-30	400Vdc	300
		0.1-50	75Vdc	2500
SCF625PFx400VD , Cartridge Type, x means rated current, 0.1A~20A	6.76 x 26.5 (0.27 x 1.04)	0.1-20	250Vac	10000
		0.1-20	400Vdc	2000
		0.1-30	400Vdc	300
		0.1-50	75Vdc	2500
SCF625PFx75V , Cartridge Type, x means rated current, 0.1A~50A	6.76 x 26.5 (0.27 x 1.04)	0.1-20	250Vac	10000
		0.1-20	400Vdc	2000
		0.1-30	400Vdc	300
		0.1-50	75Vdc	2500