

TVS Diodes

Transient Voltage Suppression Diodes

ASMA-VR Series




Description

Transient Voltage Suppressor (TVS) is a circuit protection component that either attenuates (reduces) or filters a transient voltage spike (overvoltage), TVS diodes provide critical protection by going into avalanche breakdown within no more than a few nanoseconds after a strike, clamping the transient voltage, and routing its current to the ground.

Applications

- Communication Equipment
- Security & Protection
- Industrial Control Equipment
- Power Supply
- Automotive Electronics
- New Energy
- Lightning Protection


Functional Diagram



Features

- AEC-Q101 Qualified
- Low incremental surge resistance
- Excellent clamping capability
- Low profile package with built-in strain relief
- Typical I_R less than 1.0 μA above 12 V
- 400 W peak pulse power capability with a 10/1000 μs Waveform, repetition rate (duty cycle): 0.01%
- For surface mounted applications to optimize board space
- Typical failure mode is short from over-specified voltage or current
- IEC 61000-4-2 ESD 30 kV (Air), 30 kV (Contact)
- EFT protection of data lines in accordance with IEC 61000-4-4
- Very fast response time
- Glass passivated chip junction
- High temperature to reflow soldering guaranteed: 260 °C/30 sec
- $V_{BR} @ T_J = V_{BR@25^\circ C} \times (1 + \alpha T \times (T_J - 25))$
(αT : Temperature Coefficient, typical value is 0.1%)
- Plastic package is flammability rated V-0 per Underwriters Laboratories
- Meet MSL level1, per J-STD-020
- Matte tin lead-free plated
- Halogen free and RoHS compliant
- Pb-free E3 means 2nd level interconnect is Pb-free and the terminal finish material is tin(Sn) (IPC/JEDEC J-STD-609A.01)

Package Outline Dimensions (DO-214AC)



Symbol	Millimeters		Inches	
	Min.	Max.	Min.	Max.
L	3.99	4.60	0.157	0.181
W	2.30	2.79	0.095	0.110
W ₁	1.25	1.65	0.049	0.065
H	1.90	2.44	0.075	0.096
T	0.152	0.305	0.006	0.012
L ₁	4.80	5.28	0.189	0.208
L ₂	0.78	1.52	0.030	0.060
D	-	0.203	-	0.008
A	-	2.30	-	0.090
B	2.10	-	0.082	-
C	2.10	-	0.082	-
E	1.80	-	0.070	-

Maximum Ratings and Characteristics

(Ratings at 25 °C ambient temperature unless otherwise specified.)

Parameter	Symbol	Value	Unit
Peak Power Dissipation with a 10/1000 μ s waveform ⁽¹⁾⁽²⁾ (Fig.2)-Signal Die Parts	P _{PPM}	400	W
Peak Power Dissipation with a 10/1000 μ s waveform ⁽¹⁾⁽²⁾ (Fig.2)-Stacked Die Parts ⁽⁵⁾	P _{PPM}	600	W
Peak Power Dissipation on Infinite Heat Sink at T _L =50 °C	P _D	3.3	W
Peak Forward Surge Current, 8.3 ms single half sinewave superimposed on rated load (JEDEC Method) ⁽³⁾	I _{FSM}	60	A
Maximum Instantaneous Forward Voltage at 25 A for Unidirectional Only ⁽⁴⁾	V _F	3.5/5.0	V
Operating Temperature Range	T _J	-65 to 150	°C
Storage Temperature Range	T _{STG}	-65 to 175	°C
Typical Thermal Resistance Junction to Lead	R _{θJL}	30	°C / W
Typical Thermal Resistance Junction to Ambient	R _{θJA}	120	°C / W

Notes


1. Non-repetitive current pulse, per Fig. 4 and derated above T_J(initial)=25°C per Fig. 3.
2. Mounted on 5.0 mm² land areas.
3. Measured of 8.3 ms single half sine-wave or equivalent square wave, duty cycle=4 pulses per minute maximum.
4. V_F < 3.5 V for single die parts and V_F < 5.0 V for stacked-die parts.
5. For stacked die component details, please refer to part numbers labeled by * in Electrical Characteristics.

TVS Diodes



Transient Voltage Suppression Diodes

ASMA-VR Series

Part Numbering System



Marking



Electrical Characteristics

(T_A=25 °C unless otherwise noted)Table 1

Part Number		Device Marking Code		Breakdown Voltage V _{BR} @I _T		Test Current I _T	Reverse Stand-off Voltage V _R	Max. Reverse Leakage I _R @V _R	Max. Peak Pulse Current I _{PPM}	Max. Clamping Voltage V _C @I _{PPM}
				Min	Max					
Uni	Bi	Uni	Bi	(V)		(mA)	(V)	(μA)	(A)	(V)
ASMA5.0A-VR	ASMA5.0CA-VR	AAE	AWE	6.40	7.00	10	5.00	200.00	43.50	9.20
ASMA6.0A-VR	ASMA6.0CA-VR	AAG	AWG	6.67	7.37	10	6.00	200.00	38.80	10.30
ASMA6.5A-VR	ASMA6.5CA-VR	AAK	AWK	7.22	7.98	10	6.50	150.00	35.70	11.20
ASMA7.0A-VR	ASMA7.0CA-VR	AAM	AWM	7.78	8.60	10	7.00	100.00	33.30	12.00
ASMA7.5A-VR	ASMA7.5CA-VR	AAP	AWP	8.33	9.21	1	7.50	50.00	31.00	12.90
ASMA8.0A-VR	ASMA8.0CA-VR	AAR	AWR	8.89	9.83	1	8.00	25.00	29.40	13.60
ASMA8.5A-VR	ASMA8.5CA-VR	AAT	AWT	9.44	10.40	1	8.50	10.00	27.80	14.40
ASMA9.0A-VR	ASMA9.0CA-VR	AAV	AWV	10.00	11.10	1	9.00	10.00	26.00	15.40
ASMA10A-VR	ASMA10CA-VR	AAX	AWX	11.10	12.30	1	10.00	5.00	23.50	17.00
ASMA11A-VR	ASMA11CA-VR	AAZ	AWZ	12.20	13.50	1	11.00	1.00	22.00	18.20
ASMA12A-VR	ASMA12CA-VR	ABE	AXE	13.30	14.70	1	12.00	1.00	20.10	19.90
ASMA13A-VR	ASMA13CA-VR	ABG	AXG	14.40	15.90	1	13.00	1.00	18.60	21.50
ASMA14A-VR	ASMA14CA-VR	ABK	AXK	15.60	17.20	1	14.00	1.00	17.20	23.20
ASMA15A-VR	ASMA15CA-VR	ABM	AXM	16.70	18.50	1	15.00	1.00	16.40	24.40
ASMA16A-VR	ASMA16CA-VR	ABP	AXP	17.80	19.70	1	16.00	1.00	15.40	26.00
ASMA17A-VR	ASMA17CA-VR	ABR	AXR	18.90	20.90	1	17.00	1.00	14.50	27.60
ASMA18A-VR	ASMA18CA-VR	ABT	AXT	20.00	22.10	1	18.00	1.00	13.70	29.20
ASMA20A-VR	ASMA20CA-VR	ABV	AXV	22.20	24.50	1	20.00	1.00	12.30	32.40
ASMA22A-VR	ASMA22CA-VR	ABX	AXX	24.40	26.90	1	22.00	1.00	11.30	35.50
ASMA24A-VR	ASMA24CA-VR	ABZ	AXZ	26.70	29.50	1	24.00	1.00	10.30	38.90
ASMA26A-VR	ASMA26CA-VR	ACE	AYE	28.90	31.90	1	26.00	1.00	9.50	42.10
ASMA28A-VR	ASMA28CA-VR	ACG	AYG	31.10	34.40	1	28.00	1.00	8.80	45.40
ASMA30A-VR	ASMA30CA-VR	ACK	AYK	33.30	36.80	1	30.00	1.00	8.30	48.40
ASMA33A-VR	ASMA33CA-VR	ACM	AYM	36.70	40.60	1	33.00	1.00	7.50	53.30
ASMA36A-VR	ASMA36CA-VR	ACP	AYP	40.00	44.20	1	36.00	1.00	6.90	58.10
ASMA40A-VR	ASMA40CA-VR	ACR	AYR	44.40	49.10	1	40.00	1.00	6.20	64.50
ASMA43A-VR	ASMA43CA-VR	ACT	AYT	47.80	52.80	1	43.00	1.00	5.80	69.40
ASMA45A-VR	ASMA45CA-VR	ACV	AYV	50.00	55.30	1	45.00	1.00	5.50	72.70
ASMA48A-VR	ASMA48CA-VR	ACX	AYX	53.30	58.90	1	48.00	1.00	5.20	77.40
ASMA51A-VR	ASMA51CA-VR	ACZ	AYZ	56.70	62.70	1	51.00	1.00	4.90	82.40
ASMA54A-VR	ASMA54CA-VR	ARE	AZE	60.00	66.30	1	54.00	1.00	4.60	87.10

TVS Diodes

Transient Voltage Suppression Diodes

ASMA-VR Series

Part Number		Device Marking Code		Breakdown Voltage $V_{BR}@I_T$		Test Current I_T	Reverse Stand-off Voltage V_R	Max. Reverse Leakage $I_R@V_R$	Max. Peak Pulse Current I_{PP}	Max. Clamping Voltage $V_C@I_{PP}$
				Min	Max					
Uni	Bi	Uni	Bi	(V)		(mA)	(V)	(μ A)	(A)	(V)
ASMA58A-VR	ASMA58CA-VR	ARG	AZG	64.40	71.20	1	58.00	1.00	4.30	93.60
ASMA60A-VR	ASMA60CA-VR	ARK	AZK	66.70	73.70	1	60.00	1.00	4.10	96.80
ASMA64A-VR	ASMA64CA-VR	ARM	AZM	71.10	78.60	1	64.00	1.00	3.90	103.00
ASMA70A-VR	ASMA70CA-VR	ARP	AZP	77.80	86.00	1	70.00	1.00	3.50	113.00
ASMA75A-VR	ASMA75CA-VR	ARR	AZR	83.30	92.10	1	75.00	1.00	3.30	121.00
ASMA78A-VR	ASMA78CA-VR	ART	AZT	86.70	95.80	1	78.00	1.00	3.20	126.00
ASMA85A-VR	ASMA85CA-VR	ARV	AZV	94.40	104.00	1	85.00	1.00	2.90	137.00
ASMA90A-VR	ASMA90CA-VR	ARX	AZX	100.00	111.00	1	90.00	1.00	2.70	146.00
ASMA100A-VR	ASMA100CA-VR	ARZ	AZZ	111.00	123.00	1	100.00	1.00	2.50	162.00
ASMA110A-VR	ASMA110CA-VR	ASE	AVE	122.00	135.00	1	110.00	1.00	2.30	177.00
ASMA120A-VR	ASMA120CA-VR	ASG	AVG	133.00	147.00	1	120.00	1.00	2.10	193.00
ASMA130A-VR	ASMA130CA-VR	ASK	AVK	144.00	159.00	1	130.00	1.00	1.90	209.00
ASMA150A-VR	ASMA150CA-VR	ASM	AVM	167.00	185.00	1	150.00	1.00	1.60	243.00
ASMA160A-VR	ASMA160CA-VR	ASP	AVP	178.00	197.00	1	160.00	1.00	1.50	259.00
ASMA170A-VR	ASMA170CA-VR	ASR	AVR	189.00	209.00	1	170.00	1.00	1.50	275.00
ASMA180A-VR	ASMA180CA-VR	AST	AVT	201.00	222.00	1	180.00	1.00	1.40	292.00
ASMA188A-VR	ASMA188CA-VR	ASB	AVB	209.00	231.00	1	188.00	1.00	1.40	304.00
ASMA200A-VR	ASMA200CA-VR	ASV	AVV	224.00	247.00	1	200.00	1.00	1.20	324.00
ASMA220A-VR	-	ASX	-	246.00	272.00	1	220.00	1.00	1.10	356.00
-	ASMA220CA*-VR	-	AVX	246.00	272.00	1	220.00	1.00	1.10	356.00
ASMA250A-VR	-	ASZ	-	279.00	309.00	1	250.00	1.00	1.00	405.00
-	ASMA250CA*-VR	-	AVZ	279.00	309.00	1	250.00	1.00	1.00	405.00
ASMA300A*-VR	ASMA300CA*-VR	ATE	AUE	335.00	371.00	1	300.00	1.00	0.80	486.00
ASMA350A*-VR	ASMA350CA*-VR	ATG	AUG	391.00	432.00	1	350.00	1.00	0.70	567.00
ASMA400A*-VR	ASMA400CA*-VR	ATK	AUK	447.00	494.00	1	400.00	1.00	0.60	648.00
ASMA440A*-VR	ASMA440CA*-VR	ATM	AUM	492.00	543.00	1	440.00	1.00	0.60	713.00

Notes:



- For bidirectional type having V_R of 10 volts and less, the I_R should be doubled.
- For parts without A in the PN, the V_{BR} tolerance is $\pm 10\%$ and V_C is 5% higher than parts with A. The parts without A are currently available, but not recommended for new designs. The parts with A are preferred.
- For stacked die component details, please refer to models marked with * in electrical characteristics table.

TVS Diodes

Transient Voltage Suppression Diodes

ASMA-VR Series

I-V Curve Characteristics



Performance Curve for Reference ($T_A=25^\circ\text{C}$ unless otherwise noted)




FIGURE 1 TVS Transients Clamping Waveform




FIGURE 2 Peak Pulse Power Rating Curve




FIGURE 3 Peak Pulse Power Derating Curve




FIGURE 4 Pulse Waveform

TVS Diodes

Transient Voltage Suppression Diodes

ASMA-VR Series




FIGURE 5 Typical Junction Capacitance




FIGURE 6 Typical Transient Thermal Impedance




FIGURE 7 Maximum Non-Repetitive Forward Surge Current
Uni-Directional only




FIGURE 8 Peak Forward Drop vs Peak Forward Current
(Typical Values)

Environmental Specifications

High Temp. Storage	JESD22-A103
HTRB	JESD22-A108
Temperature Cycling	JESD22-A104
MSL	JESDEC-J-STD-020, Level 1
H3TRB	JESD22-A101
RSH	JESD22-A111

Physical Specifications


Weight	0.002ounce,0.061grams
Case	JESD22DO214AC. Molded plastic body over glass passivated junction
Polarity	Color band denotes positive end (cathode) except Bidirectional
Terminal	Matte Tin-plated leads, Solderability per JESD22-B102

TVS Diodes

Transient Voltage Suppression Diodes

ASMA-VR Series

Soldering Parameters



Reflowing Condition


Reflow Soldering Parameters		Lead-Free Assembly
Pre-heat	Temperature Min ($T_{S(min)}$)	150 °C
	Temperature Max ($T_{S(max)}$)	200 °C
	Time (min to max) (t_s)	60 ~ 120 seconds
Average Ramp Up Rate (Liquidus Temp (T_L) to Peak		3 °C / second max.
$T_S(max)$ to T_L Ramp-up Rate		3 °C / second max.
Reflow	Temperature (T_L) (Liquidus)	217 °C
	Time (min to max) (t_L)	60 ~ 150 seconds
Peak Temperature (T_P)		260 ^{+0/-5} °C
Time of within 5 °C of Actual Peak Temperature (t_P)		20 ~ 40 seconds
Ramp-down Rate		6 °C / second max.
Time from 25 °C to Peak Temperature		8 Minutes max.
Do Not Exceed		260 °C


TVS Diodes

Transient Voltage Suppression Diodes

ASMA-VR Series

Packaging Information

Tape	Symbol	Dimension (mm)
	W	$12.00 \pm 0.30 / -0.10$
	P ₀	4.00 ± 0.10
	P ₁	8.00 ± 0.10
	P ₂	2.00 ± 0.05
	D ₀	1.55 ± 0.05
	D ₁	1.55 ± 0.05
	E	1.75 ± 0.10
	F	5.50 ± 0.05
	A ₀	2.79 ± 0.10
	B ₀	5.33 ± 0.10
	K ₀	2.36 ± 0.10
	T	0.30 ± 0.05

Reel Size	13" Reel	
	A	330 mm
	C	13.2 mm
	W ₁	12.5 mm

Part Number	Package	QTY (Reel)	Packaging Option	Packaging Specification
ASMAxxx-VR	DO-214AC	5000 PCS	Tape & Reel – 12 mm tape/13" reel	EIA STD RS-481
ASMAxxx-VR	DO-214AC	7500 PCS	Tape & Reel – 12 mm tape/13" reel	EIA STD RS-481

Glossary

Item	Description
V_C	Clamping Voltage Voltage across TVS in a region of low differential resistance that serves to limit the voltage across the device terminals.
V_R	Reverse Stand-off Voltage Maximum voltage that can be applied to the TVS without operation. NOTE : It is also shown as V_{WM} (maximum working voltage (maximum d.c. voltage)) and known as rated stand-off voltage (V_{so}).
I_R	Reverse Leakage Current Current measured at V_R . NOTE : Also shown as I_D for stand-by current.
V_{BR}	Breakdown Voltage Voltage across TVS at a specified current I_T in the breakdown region.
I_{PPM}	Rated Random Recurring Peak Impulse Current Maximum-rated value of random recurring peak impulse current that may be applied to a device.
$P_{M(AV)}$	Rated Average Power Dissipation Maximum-rated value of power dissipation resulting from all sources, including transients and standby current, averaged over a short period of time.
P_{PPM}	Rated Random Recurring Peak Impulse Power Dissipation Maximum-rated value of the product of rated random recurring peak impulse current (I_{PPM}) multiplies by specified maximum clamping voltage (V_C).
C_J	Capacitance Capacitance across the TVS measured at a specified frequency and voltage.
V_{FS}	Peak Forward Surge Voltage Peak voltage across an TVS for a specified forward surge current (I_{FS}) and time duration. NOTE : Also shown as V_F .
I_{FS}	Forward Surge Current Pulsed current through TVS in the forward conducting region. NOTE : Also shown as I_F .
$\alpha_{V(BR)}$	Temperature Coefficient of Breakdown Voltage The change of breakdown voltage divided by the change of temperature.
I_{PP}	Peak pulse Current Peak pulse current value applied across the TVS to determine the clamping voltage V_C for a specified wave shape.
I_T	Pulsed D.C. Test Current Test current for measurement of the breakdown voltage V_{BR} . This is defined by the manufacturer and usually given in milliamperes with a pulse duration of less than 40 ms. NOTE : Also shown as I_{BR} .

—(GB-T 18802.321 / IEC 61643-321 / JESD210A)



ATTENTION

Usage

1. TVS must be operated in the specified ambient temp.
2. Do not clean the TVS with strong polar solvent such as ketone, esters, benzene and halogenated hydrocarbon, to avoid damaging the encapsulating layer.
3. Please do not apply severe vibration, shock or pressure to TVS, to avoid element cracking.

Replacement

1. If TVS is visually damaged, please replace it.
2. TVS is a non-repairable product. For safety sake, please use equivalent TVS for replacement.

Storage

1. Storage Temp. Range: (-55 to 150) °C.
2. Do not store the TVS at the high temp., high humidity or corrosive gas environment, to avoid influencing the solder- ability of the lead wires. The product shall be used up within 1 year after receiving the goods.

Environmental Conditions

1. TVS should not be exposed to the open air, nor direct sunshine.
2. TVS should avoid rain, water vapor or other condition of high temp. and high humidity.
3. TVS should avoid sand dust, salt mist, or other harmful gases.



Max. Typical Capacitance of TVS

The typical capacitance of TVS is listed in the specifications. Designers may refer to it when designing TVS in High frequency circuit.



Installation Mechanical Stress

1. Do not knock TVS when installing, to avoid mechanical damage.
2. Please do not apply severe vibration, shock or pressure to TVS, to avoid surface resin or element cracking.

Automotive TVS Diodes (Surface Mount) Feature Overview

Package Type	Series							
	DO-214AA	DO-214AB	DO-214AC	DO-218AB	ASMB	ASMB-VR	ASMC	ASMC-VR
Product Outline (mm)								
								
$V_R / V_{WM} (V)$ Reverse Stand-off Voltage	5.8 ~ 468	5.0 ~ 440	5.8 ~ 553	5.0 ~ 440	5.8 ~ 512	5.0 ~ 440	5.0 ~ 100	12.0 ~ 170
$P_{PPM} (W)$ (10/1000 μs) Rated Peak ImPulse Power Dissipation	400		600		1500		3000	5000
Operating Temperature (°C)	-55 to +150							

Automotive TVS Diodes (Surface Mount) Feature Overview

										Page
Package Type	DO-214AA	○	○	○	○	○	○	○	○	Series
	DO-214AB	○	○	○	○	○	○	○	○	
	DO-214AC	○	○	○	○	○	○	○	○	
	DO-218AB	SM5SxxA-C	SM5SxxCA-C	SM6SxxA-C	SM6SxxCA-C	SM8SxxA-C	SM8SxxCA-C	SM8TxxA	SM8TxxCA	
Product Outline (mm)										
V_R / V_{WM} (V) Reverse Stand-off Voltage	10.0 ~ 85.0						20.0 ~ 43.0	33.0 ~ 36.0		
P_{PPM} (W) (10/1000 μ s) Rated Peak ImPulse Power Dissipation	3600	4600		6600		8000				
Operating Temperature (°C)	-55 to +175									